

# Cashmere® Customline®

PERFORMANCE SERIES MINERAL FIBER CEILING



## Specification Sheet

### Features & Benefits:

- Upscale appearance.
- Finely textured.
- Clean linear scoring.
- Scored options for added visual impact.
- Product's deep scoring complements the suspension system, masking the metal grid.
- No added formaldehyde.

See reverse for additional product specifications.

### Applications:

- Resorts
- Conference Rooms
- Airports
- Hospitality
- Retail
- Offices
- Education
- Healthcare
- Restaurants
- Salons

### Attributes:

ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	UL CLASSIFIED		LR	RECYCLED CONTENT %
			NRC	CAC		
<b>SAFETONE® CLASS A</b>						
<b>CDS-224</b>	24 x 48 x 3/4	Reveal	<b>0.60</b>	<b>35</b>	0.83	<b>74</b>
<b>CDSN-224</b>	24 x 48 x 3/4	Narrow Reveal	<b>0.60</b>	<b>35</b>	0.83	<b>74</b>
<b>CDS-448</b>	24 x 48 x 3/4	Reveal	<b>0.60</b>	<b>35</b>	0.83	<b>74</b>
<b>CDS-812</b>	24 x 48 x 3/4	Reveal	<b>0.60</b>	<b>35</b>	0.83	<b>74</b>
<b>CDSN-812</b>	24 x 48 x 3/4	Narrow Reveal	<b>0.60</b>	<b>35</b>	0.83	<b>74</b>


ASTM E 1264 Classification: Type III, Form 1, Pattern E K




### Scoring Options:



24" x 48"  
224



24" x 48"  
448




24" x 48"  
812




**BioShield™**  
BioShield™ treatment **included** for added mold and mildew resistance.



### Edge Details:



**REVEAL EDGE**  
(Beveled) 1/8" Grid



**NARROW REVEAL EDGE**  
(Beveled) 3/16" Grid

# Product Specification Details

## Acoustical Ceilings

### 09 51 00

#### PART 2: PRODUCTS

##### 2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

##### 2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 1
3. Pattern [E] [K]
4. Lightly textured surface scored to simulate [two 24" x 24"] [four 6" x 48"] [eight 12" x 12"] nodular lay-in panel
5. Size 3/4" thick x 24" x 48"
6. Edge Detail [Reveal] [Narrow Reveal]
7. Noise Reduction Coefficient (NRC) 0.60
8. Ceiling Attenuation Class (CAC) 35
9. Light Reflectance Coefficient (LR) 0.83
10. Recycled Content 74
11. Color White
12. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
13. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
14. Product Name Cashmere® Customline®

---

Distributed by:

---

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

---

#### ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE  
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777

[www.certainteed.com](http://www.certainteed.com) <http://blog.certainteed.com>

© 05/10 CertainTeed Corporation  
Code No. CTC-4665