

CertainTeed

Level V Wall and Ceiling

Primer / Surfacers with M2Tech®



- Takes a level 4 finish to level 5 efficiently
- Mold resistant, achieves highest possible score of 10 under ASTM D3273
- Sprayer or roller application
- Eliminates skim coat by hand
- More durable abrasion resistant surface
- Can be sanded but not necessary

Level V Wall and Ceiling Primer / Surfacers is a high quality PVA product applied in a production spray application to create a smooth wall finish that also gives mold resistance. It takes a level 4 finish to level 5 without the need to skim coat by hand. Level V allows the paint to absorb at the same rate over the entire gypsum surface by sealing the porosity between the joint compound and the wallboard paper surface which provides a uniform finish coat.

Product Data

CERTAINTEED CODE:	UPC CODE:	COLOR:	PACKAGE SIZE:	PACKAGE TYPE:
310096	800805100963	White	18.9 L / 5 US Gal.	Pail

COVERAGE:
Approx. 110–160 square feet (10.2–14.9 square meters) per gallon applied at 10–15 wet mils. Two coat application is optional.

RECOMMENDED MIL RATE:
Apply product at 10–15 wet mils, not to exceed 15 wet mils per application. See data spec sheet for details.

APPLICATION EQUIPMENT:
Apply Level V Wall and Ceiling Primer / Surfacers with an airless that sprays at least 1 gallon per minute, pump pressure rated at 2700-3000 psi and spray tip orifice between 0.023 and 0.031. Respirator not required but recommended. Clean tools, equipment and skin with soapy water and rinse.



CertainTeed

Level V Wall and Ceiling

Primer / Surfacer with M2Tech®

Features and Benefits

The only surfacer product on the market that meets ASTM specification for Level V finish and achieves highest possible score of 10 under ASTM D 3273.

1. Can be roller applied.

- 6 mils wet
- No overspray issues
- No need for airless spray equipment
- Can be used in occupied spaces (ie offices and homes)
- Roller nap – 1/4", 3/8" or 1/2" roller
The smaller the nap, the less stipple

2. Serves as Level V surface coat and prime coat all in one / no priming required

- Save time and effort
- Much easier to apply than a skim coat
- Seals wallboard surface to equalize porosity

3. Can also be spray applied utilizing conventional airless spray equipment

- No need to use heavy-duty equipment
- One product can function for all types of applications
- Spray application / 10-15 wet mils not to exceed 15 wet mils
- Use airless with output of at least 1 gpm
- Pump pressure rated at 2700-3000 psi
- Spray tip of orifice between 0.023 to 0.031

4. Coverage: 110-160 square feet (10.2–14.9 square meters) per gallon applied at 10 – 15 mils for spray application

5. Can be thinned by adding no more than one pint of water per five gallons.

- Do not over thin as over thinning could affect product performance



6. Can be sanded

- NOT NECESSARY to achieve level 5 finish!
- Helps if there is imperfections in the level 4 filling coat
- Allows repair if applicator improperly rolls on product and leaves roller marks

7. LEED Compliant

- Regional materials (MR credit 5.1) (for PNW only)
- Recycle content (MR credit 4.1)
- Low emitting material/VOC emissions (EQ credit 4.2)

8. Fast Drying

- 4 – 6 hours dependant on air temperature and relative humidity

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

© 12/10 CertainTeed Gypsum Canada, Inc. Printed in Canada.
December 2010 Code No. CTG-4034