


(Material) Safety Data Sheet



Section 1 - Product and Company Identification

- Material Name** ▪ **Asphalt Rolled Roofing**
- Product Code** ▪ CT-10122-2
- Product Description** ▪ Modified Bitumen Rolled Roofing.
- Synonyms** ▪ Flintlastic® FR-P; Flintlastic® FR-P CoolStar; Flintlastic® GTS-FR; Flintlastic® Premium FR-P; Flintlastic® Premium FRP CoolStar; Flintlastic® GTS-FR CoolStar
- Manufacturer** ▪ CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482-0101
United States
www.certainteed.com
CertainTeed - EHS@saint-gobain.com
- Telephone**
 - Technical** ▪ (610) 341-7000 - 9 AM – 5 PM (Eastern Time – USA)
 - Emergency** ▪ (800) 424-9300 - Chemtrec
 - Emergency** ▪ (703) 527-3887 - Outside of the U.S. Chemtrec
- Preparation Date** ▪ 08/01/1994
- Last Revision Date** ▪ 03/10/2011
- Key to abbreviations**
‡ = HMIS is a registered trademark of the American Coatings Association

Section 2 - Hazards Identification

Emergency Overview

- Prevention** Avoid breathing dust, fume, gas, mist, vapours and/or spray.
- Storage/Disposal** Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Under normal conditions of use the products listed in this MSDS are not expected to pose a physical hazard or health risk to humans. These products do not contain any form of asbestos materials. The component exposure limits and other information in this document are provided for circumstances such as heating (above 250°F), burning, cutting, sanding and/or grinding when there is potential for exposure to these components. If heated, this product may cause temporary irritation to the upper respiratory system. Avoid inhalation as temporary irritation may occur. Mechanical irritation may occur. Wear appropriate personal protective equipment as described in Section 8.

- Physical Form** ▪ Solid
- Color** ▪ Black
- Odor** ▪ Mild petroleum odor.
- OSHA** ▪ None
- WHMIS** ▪ None

- GHS**
- None
- Route Of Entry**
- Inhalation, Skin, Eye
- Medical Conditions Aggravated by Exposure**
- Pre-existing lung conditions which may be aggravated if fumes/dusts are inhaled,

Potential Health Effects

Inhalation

- Acute (Immediate)**
- Chronic (Delayed)**

- Temporary irritation of nose and throat may occur.
- This product contains crystalline silica which is listed by IARC as a suspect carcinogen. Silicosis (pulmonary fibrosis or severe lung scarring) may occur if exposed to high levels or repeated encounters with dust. Exposure to airborne particles that exceed the limits listed may cause lung cancer. This product also contains petroleum asphalt. If heated, there is limited evidence that derivatives of asphalt fumes may cause carcinogenic effects in animals. There is inadequate evidence to support that asphalt fumes alone are carcinogenic to humans.

Skin

- Acute (Immediate)**
- Chronic (Delayed)**

- Mechanical irritation of the skin may occur.
- No data available.

Eye

- Acute (Immediate)**
- Chronic (Delayed)**

- Mechanical irritation of the eyes may occur.
- No data available.

Ingestion

- Acute (Immediate)**
- Chronic (Delayed)**

- Ingestion of this product unlikely.
- No data available.

Carcinogenic Effects

- When used under normal conditions, this product is not considered a carcinogen. This product contains petroleum asphalt. Asphalt fumes arise from hot asphalt. Asphalt fumes (CAS # 8052-42-4): In 1985/87, IARC (International Agency for Research on Cancer) concluded the following: (a) Bitumens are not classifiable as to their carcinogenicity to humans (Group 3). (b) Extracts of steam - and air-refined bitumens are possibly carcinogenic to humans (Group 2B). IARC found that evidence for carcinogenicity from animal studies was: inadequate for undiluted air -refined bitumens; limited for steam-refined and cracking residue bitumens; sufficient for extracts of steam-refined and air-refined bitumen. IARC found that human evidence for carcinogenicity of asphalt fumes was inadequate. Studies of roofers indicated an excess of cancers; however, IARC concluded that, since roofers may be exposed also to coal-tar pitches and other materials, "the excess cancer risk cannot be attributed specifically to bitumens." In 1994, a published review of 20 epidemiology studies of asphalt workers and roofers agreed with IARC, that current human evidence is inadequate for the carcinogenicity of asphalt fumes in humans. Trace amounts of polynuclear aromatic hydrocarbons (PAHs) may be present in some asphalts and can be released upon excessive heating, which results in thermal cracking of the asphalt compounds. Some of these PAHs have been identified as having the potential to induce carcinogenic and reproductive health effects. This product contains crystalline silica. IARC Monographs on Evaluation of Carcinogenic Risk of Chemicals to Humans (Monograph 68, 1997) concludes that there is sufficient evidence for the carcinogenicity of crystalline silica to humans, IARC (Group I). Crystalline Silica is classified as a Known Carcinogen according to the NTP.

Carcinogenic Effects			
	CAS	IARC	NTP
Quartz (SiO ₂)	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen
Asphalt	8052-42-4	Group 2B-Possible Carcinogen	Not established
		Group 3-Not Classifiable	

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

Hazardous Components						
Chemical Name	CAS	%(weight)	UN;EINECS	LD50/LC50	EU Classification & R Phrases	Other
Asphalt	8052-42-4	35% TO 55%	NA1999, 232-490-9	Ingestion/Oral-Rat LD50: >5000 mg/kg Inhalation-Rat LC50: >94.4 mg/m ³	NDA	NDA
Quartz (SiO ₂)	14808-60-7	15% TO 35%	NDA	NDA	NDA	NDA
Non-Hazardous Components						
Chemical Name	CAS	%(weight)	UN;EINECS	LD50/LC50	EU Classification & R Phrases	Other
ATH (Aluminum trihydrate)	NDA	< 20%	NDA	NDA	NDA	NDA
Colemanite	1318-33-8	< 10%	NDA	NDA	NDA	NDA
Polyester	NDA	< 10%	NDA	NDA	NDA	NDA
SBS Polymer	NDA	< 10%	NDA	NDA	NDA	NDA

Under United States Regulations (29 CFR 1910.1200(c) - Hazard Communication Standard), the product(s) listed above are exempt as article(s) under stated normal conditions of use. Under Canadian regulations (Workplace Hazardous Materials Information System (WHMIS) - Hazardous Products Act (HPA), Section 11(1)), these product(s) are exempt and considered manufactured article(s) under stated normal conditions of use. Under United Nations Globally Harmonized System for the Classification and Labeling of Hazardous Chemicals (GHS) this product is exempt from regulation as a manufactured article.

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

- | | |
|-------------------|---|
| Inhalation | <ul style="list-style-type: none"> Remove to fresh air, apply artificial respiration and/or oxygen if necessary and get medical attention. |
| Skin | <ul style="list-style-type: none"> Remove contaminated clothing and wash exposed skin with soap and water. If irritation develops or persists, seek medical attention. |
| Eye | <ul style="list-style-type: none"> If foreign matter enters eyes, immediately flush with large amounts of water for at least 15 minutes or until irritation subsides. If irritation develops, or persists, seek medical attention. |
| Ingestion | <ul style="list-style-type: none"> Consult a physician if unusual reaction is noted. Product is not intended nor is it likely to be ingested or eaten. |

See Section 2 for Potential Health Effects.

Section 5 - Fire Fighting Measures

- | | |
|---|--|
| Extinguishing Media | <ul style="list-style-type: none"> Use water, foam, CO₂ or dry chemical extinguishers to contain fire. |
| Unsuitable Extinguishing Media | <ul style="list-style-type: none"> No data available. |
| Firefighting Procedures | <ul style="list-style-type: none"> Fire fighters should avoid inhaling any combustion products. |
| Unusual Fire and Explosion Hazards | <ul style="list-style-type: none"> Burning of this product will produce thick black smoke. |
| Hazardous Combustion Products | <ul style="list-style-type: none"> If burned, the materials could release toxic fumes and smoke. Incomplete thermal oxidation can produce hydrogen cyanide, carbon monoxide, carbon dioxide, ammonia, formaldehyde and other low molecular weight hydrocarbons and oxides or sulfur, nitrogen, calcium and magnesium. |

- Protection of Firefighters**
 - Firefighters should wear full-face, self contained breathing apparatus and impervious protective clothing to avoid smoke inhalation and lack of oxygen.

Section 6 - Accidental Release Measures


- Personal Precautions**
 - Not applicable.
- Emergency Procedures**
 - Not applicable.
- Containment/Clean-up Measures**
 - Pick up large pieces. Vacuum dust. If sweeping is necessary, use a dust suppressant such as water. These procedures will help to minimize potential exposures. Scoop up material and put into a suitable container for disposal as a non-hazardous waste.

Section 7 - Handling and Storage

- Handling**
 - Do not breathe dusts or fumes generated from cutting or heating this material. Keep this product away from heat, sparks, or open flame. Use this product with adequate ventilation. Always wash work clothes separately from other clothing. Wash thoroughly after handling. Use personal protective equipment as described in Section 8.
- Storage**
 - Store indoors in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition.
- Special Packaging Materials**
 - No data available.
- Incompatible Materials or Ignition Sources**
 - This product will react with strong oxidizing agents, reducing agents, strong acids and alkalis.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

- Pictograms**
 - 
- Respiratory**
 - Respiratory protection is not normally required. Use a NIOSH approved/certified respiratory when the exposure limits are exceeded. Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.
- Eye/Face**
 - Safety glasses with side shields should be worn at a minimum.
- Hands**
 - Leather or cotton gloves may be worn to prevent skin contact and irritation.
- Skin/Body**
 - Normal work clothing (long sleeved shirts and long pants) is recommended.
- General Industrial Hygiene Considerations**
 - Use good industrial hygiene practices in handling this material. Availability of eye wash fountains are recommended.
- Engineering Measures/Controls**
 - No special ventilation systems are required under normal conditions of use.

Exposure Limits/Guidelines						
	Result	ACGIH	Canada British Columbia	Canada Manitoba	Canada New Brunswick	Canada Northwest Territories
Quartz (SiO ₂) (14808-60-7)	TWAs	0.025 mg/m ³ TWA (respirable fraction)	0.025 mg/m ³ TWA (respirable)	0.025 mg/m ³ TWA (respirable fraction)	0.1 mg/m ³ TWA (respirable fraction)	0.1 mg/m ³ TWA (respirable mass); 0.3 mg/m ³ TWA (total mass)
Asphalt (8052-42-4)	TWAs	0.5 mg/m ³ TWA (as benzene soluble aerosol, fume, inhalable fraction)	0.5 mg/m ³ TWA (as benzene-soluble aerosol, inhalable fume)	0.5 mg/m ³ TWA (as benzene soluble aerosol, fume, inhalable fraction)	5 mg/m ³ TWA (petroleum fumes)	5 mg/m ³ TWA
	STELs	Not established	Not established	Not established	Not established	10 mg/m ³ STEL

Exposure Limits/Guidelines (Con't.)						
	Result	Canada Nova Scotia	Canada Nunavut	Canada Ontario	Canada Quebec	Canada Yukon
Quartz (SiO ₂) (14808-60-7)	TWAs	0.025 mg/m ³ TWA (respirable fraction)	0.1 mg/m ³ TWA (respirable mass); 0.3 mg/m ³ TWA (total mass)	0.10 mg/m ³ TWAEV (designated substance regulation)	0.1 mg/m ³ TWAEV (respirable dust)	300 particles/mL TWA
Asphalt (8052-42-4)	TWAs	0.5 mg/m ³ TWA (as benzene soluble aerosol, fume, inhalable fraction)	5 mg/m ³ TWA	0.5 mg/m ³ TWAEV (fume, inhalable, as benzene-soluble aerosol)	5 mg/m ³ TWAEV (fume)	5 mg/m ³ TWA (fume)
	STELs	Not established	10 mg/m ³ STEL	Not established	Not established	10 mg/m ³ STEL (fume)

Exposure Limits/Guidelines (Con't.)			
	Result	NIOSH	United States - California
Quartz (SiO ₂) (14808-60-7)	TWAs	0.05 mg/m ³ TWA (respirable dust)	0.3 mg/m ³ PEL (total dust); 0.1 mg/m ³ PEL (respirable dust)
Asphalt (8052-42-4)	TWAs	Not established	5 mg/m ³ PEL (fume)
	Ceilings	5 mg/m ³ Ceiling (fume, 15 min)	Not established

Exposure Limits Supplemental

OSHA

• Quartz (SiO₂) (14808-60-7): **Mineral Dusts:** ((30)/(%SiO₂ + 2) mg/m³ TWA, total dust; (250)/(%SiO₂ + 5) mppcf TWA, respirable fraction; (10)/(%SiO₂ + 2) mg/m³ TWA, respirable fraction)

Key to abbreviations

PEL = Permissible Exposure Level determined by the Occupational Safety and Health Administration (OSHA)

TWAEV = Time-Weighted Average Exposure Value

STEL = Short Term Exposure Limits are based on 15-minute exposures

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

Section 9 - Physical and Chemical Properties

Physical Form

- Solid

Appearance/Description

- Black asphalt roofing rolls with mild petroleum odor.

Color : Black	Odor : Mild petroleum odor.
---------------	-----------------------------

Taste : No data available.		Odor Threshold : NDA	
Boiling Point:	NDA	Vapor Pressure:	NDA
Melting Point:	NDA	Vapor Density:	NDA
Specific Gravity:	NDA	Evaporation Rate:	NDA
Density:	NDA	VOC (Wt.):	NDA
Bulk Density:	NDA	VOC (Vol.):	NDA
pH:	NDA	Volatiles (Wt.):	NDA
Water Solubility:	Insoluble	Volatiles (Vol.):	NDA
Solvent Solubility:	NDA	Flash Point:	NDA
Viscosity:	NDA	Flash Point Test Type:	NDA
Half-Life:	NDA	UEL:	NDA
Octanol/Water Partition coefficient:	NDA	LEL:	NDA
Coefficient of water/oil distribution:	NDA	Autoignition:	NDA
Bioaccumulation Factor:	NDA	Bioconcentration Factor:	NDA
Biochemical Oxygen Demand BOD/BOD5:	NDA	Chemical Oxygen Demand:	NDA
Persistence:	NDA	Degradation:	NDA

Section 10 - Stability and Reactivity

- | | |
|---|---|
| Stability | <ul style="list-style-type: none"> Stable under normal conditions of use. |
| Hazardous Polymerization Conditions to Avoid | <ul style="list-style-type: none"> Hazardous polymerization will not occur. |
| Incompatible Materials | <ul style="list-style-type: none"> Keep away from heat, ignition sources and incompatible materials. This product will react with strong oxidizing agents, reducing agents, strong acids and alkalis. |
| Hazardous Decomposition Products | <ul style="list-style-type: none"> Upon decomposition this product may emit hydrogen sulfide, formaldehyde, hydrogen cyanide, carbon dioxide, carbon monoxide and other low molecular weight hydrocarbons and oxides of sulfur, nitrogen, calcium and magnesium. |

Section 11 - Toxicological Information

Temporary irritation may be observed in the upper respiratory system, eyes, and skin. Inhalation of dusts/fumes from this product may cause scratchy throat, congestion, and slight coughing.

Component Name	Concentration	CAS	Data
Asphalt	35% TO 55%	8052-42-4	Acute Toxicity: orl-rat LD50:>5000 mg/kg; ihl-rat LC50:>94.4 mg/m3; ihl-rat TCLo:100 mg/m3/6H/14W-I; ihl-hmn TDL0:10 mg/m3/5.5Y-I
Quartz (SiO2)	15% TO 35%	14808-60-7	Acute Toxicity: ihl-hmn LCLo:300 ug/m3/10Y-I; ihl-rat TCLo:6.2 mg/m3/6H/6W-I; ihl-rat TCLo:108 mg/m3/6H/3D-I; ihl-rat TCLo:200 mg/kg; Tumorigen/Carcinogen: ihl-rat TCLo:50 mg/m3/6H/71W-I

This product contains crystalline silica. Crystalline silica is considered a carcinogen by IARC as well as NTP. This product contains petroleum asphalt. If heated, there is limited evidence that derivatives of asphalt fumes may cause carcinogenic effects in animals. There is inadequate evidence to support that asphalt fumes alone are carcinogenic to humans.

Section 12 - Ecological Information

- | | |
|----------------------------------|---|
| Ecological Fate | <ul style="list-style-type: none"> No information available for the product. |
| Persistence/Degradability | <ul style="list-style-type: none"> No information available for the product. |

Bioaccumulation Potential ▪ No information available for the product.

Mobility in Soil ▪ No information available for the product.

This product has not been tested. Based on information related to all raw materials in the finished product it is not expected to harm ecosystems through its applied use.

Section 13 - Disposal Considerations

Product ▪ This product, as supplied, is not regulated as a hazardous waste by the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Comply with state and local regulations for disposal. If you are unsure of the regulations, contact your local public health department, or the local office of the EPA. Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - Transportation Information

DOT - United States - Department of Transportation

Shipping Name: Not Regulated

TDG - Canada - Transport of Dangerous Goods

Shipping Name: Not Regulated

Section 15 - Regulatory Information

SARA Hazard Classifications ▪ None

State Right To Know					
Component	CAS	MA	MN	NJ	PA
ATH (Aluminum trihydrate)	NDA	No	No	No	No
Colemanite	1318-33-8	No	No	No	No
Polyester	NDA	No	No	No	No
SBS Polymer	NDA	No	No	No	No
Asphalt	8052-42-4	Yes	Yes	Yes	Yes
Quartz (SiO2)	14808-60-7	Yes	Yes	Yes	Yes

Inventory		
Component	CAS	TSCA
ATH (Aluminum trihydrate)	NDA	No
Colemanite	1318-33-8	No
Polyester	NDA	No
SBS Polymer	NDA	No
Asphalt	8052-42-4	Yes
Quartz (SiO2)	14808-60-7	Yes

Canada

Labor

Canada - List of Prohibited and Restricted Cosmetic Ingredients (The Cosmetic Ingredient Hotlist)

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

Canada - WHMIS - Classifications of Substances

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS website.)
- Colemanite 1318-33-8 < 10% Not Listed

Canada - WHMIS - Ingredient Disclosure List

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% 1 %
- Colemanite 1318-33-8 < 10% Not Listed

United States

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CWA (Clean Water Act) - Bioaccumulative Chemicals of Concern (BCCs)

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO₂) 14808-60-7 15% TO 35% Not Listed

- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CWA (Clean Water Act) - Hazardous Substances

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO2) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - CWA (Clean Water Act) - Priority Pollutants

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO2) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - EPA - Priority PBT List

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO2) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - FIFRA - Listing of Pesticide Chemicals (40 CFR 180)

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO2) 14808-60-7 15% TO 35% Section number 180.910
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - FIFRA - Pesticide Product Other Ingredients

- Asphalt 8052-42-4 35% TO 55% List 3 - Unknown Toxicity
- Quartz (SiO2) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO2) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

U.S. - TSCA (Toxic Substances Control Act) - Section 8(a) - Inventory Update Rule - Partially Exempt Substances

- Asphalt 8052-42-4 35% TO 55% Partially exempt chemical substance termed Petroleum Process Stream
- Quartz (SiO2) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO2) 14808-60-7 15% TO 35% carcinogen, initial date 10/1/88 (airborne particles of respirable size)
- Colemanite 1318-33-8 < 10% Not Listed

United States - New Jersey

Environment

U.S. - New Jersey - Special Health Hazards Substances List

- Asphalt 8052-42-4 35% TO 55% flammable - third degree
- Quartz (SiO2) 14808-60-7 15% TO 35% carcinogen
- Colemanite 1318-33-8 < 10% Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

- Asphalt 8052-42-4 35% TO 55% Not Listed
- Quartz (SiO2) 14808-60-7 15% TO 35% Not Listed
- Colemanite 1318-33-8 < 10% Not Listed

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

- Asphalt 8052-42-4 35% TO 55% Toxic; Flammable
- Quartz (SiO2) 14808-60-7 15% TO 35% Toxic (dust and fiber)
- Colemanite 1318-33-8 < 10% Not Listed

Additional Regulatory Information

- **WARNING:** This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

- Preparation Date** ▪ 08/01/1994
- Last Revision Date** ▪ 03/10/2011

Disclaimer/Statement of Liability

- Reasonable care has been taken in the preparation of this information, but the supplier gives no warranty of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser will make his own tests to determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental and/or consequential property damage arising out of the use of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Read the Material Safety Data Sheet before handling product.

Key to abbreviations
NDA = No Data Available