

**CertainTeed Corporation**  
750 E. Swedesford Road  
Valley Forge, Pennsylvania  
USA 19482-0105

Tel.: (610) 341-6826  
Fax: (610) 341-7571

**DESCRIPTION:**

“InsulSafe” loose-fill mineral-fibre insulation is composed of rotary glass fibres and a dust suppressant.

**EVALUATION:**

Conforms to CAN/ULC-S702-97, Type 5. The design thermal resistance value is  $18.5 \text{ m}^2 \text{ KW}^{-1}/\text{m}$  at a design density of  $9.78 \text{ kg}/\text{m}^3$  for products manufactured at the following plants:  
– Athens, Georgia; and  
– Chowchilla, California.

**APPROPRIATE USAGE:**

Pneumatic methods of installation only. This product shall be installed as outlined in the Preface and according to the following application chart:

**CCMC 13141-L**

Issued:  
2003-12-09

Re-evaluated:  
2007-07-17

Re-evaluation due:  
2009-12-09

Thermal Resistance ( $\text{m}^2 \cdot \text{K}/\text{W}$ )	Minimum Mass Per Unit Area ( $\text{kg}/\text{m}^2$ )	Minimum Thickness <sup>(1)</sup> (mm)	Maximum Coverage Per 13.2-kg Bag ( $\text{m}^2$ )
2.1	1.1	113	11.9
2.8	1.5	151	8.9
3.5	1.8	189	7.1
4.2	2.2	227	5.9
4.9	2.6	265	5.1
5.3	2.8	286	4.7
5.6	3.0	302	4.5
6.3	3.3	340	4.0
7.0	3.7	378	3.6
7.7	4.1	416	3.2
8.4	4.4	454	3.0
8.8	4.6	475	2.8
9.1	4.8	492	2.7
9.8	5.2	529	2.5
10.5	5.5	567	2.4

(1) The thickness at which the insulation achieves the stated thermal resistance (design thickness).