


# Technical Data Sheet

Cedar Crest™ Shingle  
(Hip and Ridge Accessory)



## PRODUCT DESCRIPTION

Cedar Crest™ is a self-sealing shingle of multiple-layered construction that combines enhanced thickness, algae resistance, and durability with flexibility and good looks. Available in 12" x 36" overall, with perforations for easy separation and yielding three 12" x 12" caps with an 8" exposure. Availability depends on sales region.



**Color:** Please refer to the product brochure or CertainTeed website for the colors available in your region. Cedar Crest shingles are designed to blend with all of CertainTeed Landmark Series and Presidential Series shingles. Cedar Crest accessory shingles will also blend closely with several competitive colors. Please review CertainTeed's Cedar Crest Color Chart for specific recommendations. Available in Algae Resistant (AR) colors only.

**Limitations:** Use on hips & ridges of roofs only after application of primary roofing shingles to both intersecting roof decks. These shingles are designed to be used with CertainTeed's shingles that reference the use of "Cedar Crest" or "High Profile Shingles". Use "Cedar Crest" product colors that complement the shingle colors applied to the main roof. Special hand-sealed application is required for 110-mph wind resistance. Contact CertainTeed's Technical Service Department @ 1-800-345-1145 for details or refer to this information on the wrapper.

**Product Composition:** Cedar Crest shingles are composed of a fiber glass mat base. Ceramic coated mineral granules are tightly embedded in specially refined, water-resistant asphalt. This is a three-piece shingle that must be separated into individual pieces, each 12" x 12", by folding along the perforated lines.

## Applicable Standards:

ASTM D 3018, Type I

ASTM D 3462

ASTM E 108 Fire Resistance: Class A

UL 790 Fire Resistance: Class A

UL997 Wind Resistance

ASTM D 3161, Class F\* Wind Resistance

NYC-MEA-120-79-M

\*Special hand-sealed application required (Contact CertainTeed's Technical Service Department @ 1-800-345-1145 for details).

## TECHNICAL DATA

Weight/Bundle (approx.):	53 lb
Dimensions (overall):	12" x 36"
Separated into individual pieces:	12" x 12"
Weather Exposure:	8"
Coverage/bundle:	20 lin. ft.

## INSTALLATION

Each bundle of Cedar Crest shingles has detailed installation instructions including diagrams.

## AVAILABILITY AND COST

Availability: For the names of local distributors and dealers, please write Architectural Support, P.O. Box 860, Valley Forge, PA 19482; or call (800) 233-8990.

Cost: Contact a local distributor or dealer for current price information.

## MAINTENANCE

Cedar Crest shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

**WARRANTY**

This product has a limited warranty against manufacturing defects concurrent with the warranty of the field shingle with which it is installed.

**TECHNICAL SERVICE**

Complete technical support and assistance is available through CertainTeed's Technical Service Department @ 1-800-345-1145, Territory Managers, and the fully staffed and equipped Research and Development facility in Blue Bell, PA.

**FOR MORE INFORMATION**

Sales Support Group: 800-233-8990

Web site: [www.certainteed.com](http://www.certainteed.com)

**CertainTeed Roofing**  
P.O. Box 860  
Valley Forge, PA 19482

© Copyright CertainTeed Corporation, 2011.  
All rights reserved. Updated: 12/2011

