

FLINTFAST™ SIPLD FASTENERS

Product Information



Description: FlintFast Fasteners from CertainTeed are engineered to provide top quality performance with commercial roofing systems and designed to increase strength and improve application efficiency. SIPLD Fasteners are used in roofing applications for the attachment of nailboard (FlintBoard™ ISO NB) and vented nailboard (FlintBoard™ CV).

Uses: Light duty, #2 drill point fasteners for steel and wood deck applications. Available in lengths from 3" to 18".

Technical Data

Material: Case hardened and tempered carbon steel
Headstyle/Drive: Pancake head with T-30 internal drive
Head Diameter: 0.062"
Nominal Shank Diameter: 0.190"
Thread Length: 2.750"
Point: #2 (0.135" diameter)
Drill Point Coating: Epoxy e-coat (black)
Withdrawal Value in Wood*: 1067 lb./in.
*Specify Gravity: 0.50
Withdrawal Value in 22 ga. Steel: 510 lbf.
Approvals: Factory Mutual



Packaging

Screw Length	Pieces per Pail
3"-8"	500
8-1/2" to 18"	250

Two T-30 driver bits included in each pail.

ASK ABOUT OUR OTHER CERTAINTEED PRODUCTS AND SYSTEMS:

EXTERIOR: ROOFING • SIDING • WINDOWS • FENCE • RAILING • TRIM • DECKING • FOUNDATIONS • PIPE
INTERIOR: INSULATION • GYPSUM • CEILINGS

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
www.certainteed.com

CertainTeed 