

Technical Data Sheet

ShingleFelt™ 15

ShingleFelt™ 30



PRODUCT INFORMATION

ShingleFelt 15 and ShingleFelt 30 are utility-grade asphalt-impregnated organic felt underlayments designed for use on roof decks as a water-resistant layer beneath roofing shingles and wood shakes.

Technical Data:	ShingleFelt 15	ShingleFelt 30	ShingleFelt 30
Roll Size (sq. ft.):	432 (4 squares)	432 (4 squares)	216 (2 squares)
Roll Coverage (sq. ft.):	400	400	200
Roll Length (ft.):	144	144	72
Roll Width (ft.):	3	3	3
Shipping Weight (approx. lb/roll):	36	47	23
ASTM D4869	Type I	Type I	Type I

INSTALLATION

Storage: Store rolls on their ends in a dry, protected area at a temperature less than 120°F.

Deck Preparation: Provide a clean, dry and smooth deck surface by eliminating dust, dirt, loose nails and other objects. Before application to existing roofs, remove all roofing materials, then clean the roof deck until it is free of any dirt, dust, nails, and other materials.

Limitations: This product is not designed to be permanently exposed to sunlight or to the weather. Minimum application slope is 2" per foot. Between slopes of 2" per foot up to 4" per foot apply two layers in "shingle-fashion."

MAINTENANCE

ShingleFelt requires virtually no maintenance when installed according to manufacturer's application instructions.

WARRANTY

None.

FOR MORE INFORMATION

Sales Support Group: 800-233-8990

Web site: www.certainteed.com

See us in Sweets and ARCAT printed and electronic publications

CertainTeed Roofing

P.O. Box 860

Valley Forge, PA 19482

© Copyright CertainTeed Corporation, 2009.
All rights reserved. 12/2009

